

# Klingstone *PATHS*

*keep it together*

## Technical Data Hydrophobic Polyurethane System

### Pathways, Patios, Driveways

**Description:** Klingstone Paths is a moderate viscosity, single component, moisture curing liquid designed to stabilize aggregate for foot traffic and light vehicular traffic. It has been used on pathways at historic sites to meet ADA requirements and also on private and public sites to reduce routine maintenance while preserving a natural appearance.

**Application:** Pour or pump onto aggregate to be stabilized. Do not spray (atomize). Allow 24 hours to cure. If rain is expected, or if overnight temperatures fall below 50°F, the treated area should be covered with a plastic tarp. Coverage rates will vary with soil conditions. Typical coverage is 10 to 12 square feet per gallon.

Typical Properties	
Appearance	Amber Liquid
Viscosity @ 77°F	400 CPS
Weight per gallon	9.7 pounds
%Solids	100
Odor (liquid)	Mild
Cure Time	24 Hours
USDOT Shipping Data	UNREGULATED CLASS 55

MSDS should be read before using Klingstone products.



KlingstonePaths, LLC. Ph: 800-942-5151 Fax: 888-632-5360 Int'l: 828-456-9970

Fax: 828-456-9699 - 235 Pigeon St. Waynesville, NC 28786

URL: <http://www.klingstonepaths.com> E-mail: [sales@klingstonepaths.com](mailto:sales@klingstonepaths.com)